

SILK[®] Portable Machine Tools

AX0-8 Flange Facer

MACTECH



O/D Mounted Flange Facer AX0-8 Machine



*Mactech is a valued reseller
and exclusive distributing agent
for Silk machines in
North and South America*

The AX0-8 Flange Facer and Grooving Machine is the smallest and lightest of the SILK® Portable Machine range. The compact design and lightweight construction 18kg (40lbs) makes it the ideal choice in confined spaces while allowing for single operator use. Externally mounted, with a working range of 0 to 203mm (8") and including either 3 or 4 clamping feet to suit applications. A single in-line 0.63kW (0.84hp) pneumatic motor drives the toolpost, with pre-determined settings on the toolpost to suit standard machine angles (0°, 15° & 23°). The machine offers the capability for a single automatic or manual feed rate. Optional extras include a mounting plate to allow simple machine removal when machining a ring type joint face (RTJ)

MACHINE FEATURES:

- + Range 0" to 8" (0mm to 203.2mm)
- + Automatic feed
- + Ergonomically designed
- + Quick set-up



MACHINE:

AX0-8 Flange Facing Machine—Raised Face Only	Part No: KIT01-599-000135
AX0-8 Flange Facing Machine—Raised Face and RTJ	Part No: KIT01-599-000136

OPTIONAL EXTRAS:

AX08 - RTJ Mount Kit	Part No: KIT01-599-000138
2 Year Recommended Spares Kit	Part No: KIT01-599-000137
Toolkit	Part No: KIT01-599-000130
Pneumatic Safety Unit (PSU)	Part No: KIT01-599-000132

All dimensions and hydraulic requirements are for reference and may be subject to change without notice. Machine performance is subject to application and operator capability; please discuss your requirements directly with a Mactech sales representative. All information given and all sales made by Mactech Inc. are subject to their terms and conditions.

MACTECH INC.
4079 PEPIN AVE UNIT 4
RED WING MN 55066
800-328-1488
INFO@MACTECHONSITE.COM

MACTECH OFFSHORE
302 IDA ROAD
BROUSSARD LA 70518
337-839-2793
INFO@MACTECHOFFSHORE.COM

MACTECH KENTUCKY
3880 INDUSTRIAL DRIVE
PADUCAH KY 42001
270-442-1559
INFO@MACTECHONSITE.COM

MACTECH WISCONSIN
2515 CLEVELAND AVE
MARINETTE WI 54143
800-328-1488
INFO@MACTECHONSITE.COM

MACTECH INTERNATIONAL
CONTACT US FROM ANYWHERE
AROUND THE WORLD
337-839-2793
INFO@MACTECHOFFSHORE.COM

WORK HARD

WORK SAFE

WE BEFORE ME

WELCOME CHALLENGES

WOW THEM

OPERATING DIMENSIONS:

FACING RANGE:		
Minimum Diameter	0mm	0"
Maximum Diameter	203.2mm	8"

CLAMPING RANGE:		
Minimum Diameter	98mm	3.85"
Maximum Diameter	216mm	8.5"

TECHNICAL DETAILS:		
Toolpost Travel	30mm	1.18"
Recommended Air Supply	6Bar @ 0.86m ³ /min	30.4cfm @ 87psi
Noise Emission (Sound Power Level)	96dB(A)	

FEED RATES / POSITION:		
1	0.4mm	0.016"

WEIGHTS:		
Machine Weight	23kg	50lbs
Recommended Air Supply	33kg	180lbs

TRANSPORTATION DIMENSIONS:					
Length		Width		Height	
627mm	24.7"	303mm	11.9"	479mm	18.9"

