



I/D Mounted Flange Facer

SX28-72 Machine




Mactech is a valued reseller and exclusive distributing agent for Silk machines in North and South America

The SX28-72 Flange Facing machine is normally bore mounted, but is equally at home when surface mounted and being used for refurbishing heat exchanger gasket surfaces. The SX28-72 machine covers a range of flanges from 711mm (28") internal diameter to 1829mm (72") external diameter. The turntable incorporates twin 1.7kW (2.3hp) pneumatic motors, which are designed to compensate for the backlash normally found in spur gear drive systems. The bore mounting base has four sectional legs that ensure precise adjustment while maintaining proper rigidity, even when fully extended. The modular design also makes the SX28-72 easy to set up with any of the optional tube sheet and outside diameter mounting kits, which are available on request.

MACHINE FEATURES:

- + Range 28" to 72" (711.2mm to 1828.8mm)
- + Proven durability over many decades
- + Automatic feed
- Ergonomically designed
- Quick set-up



MACHINE:	
FXB6-30 Flange Facing Machine	Part No.: FMG55-599-000193

OPTIONAL EXTRAS:	
V-Groove Machining Kit	Part No.: KIT01-599-000082
V-Groove Measuring Kit	Part No.: KIT01-599-000083
V-Groove Measuring Kit (Vernier Height Gauge)	Part No.: KIT01-599-000113
Tube Sheet Machining Kit	Part No.: KIT01-599-000086
Tube Sheet Mounting Kit	Part No.: KIT01-599-000085
Lens Ring Machining Kit	Part No.: KIT01-599-000084
Slide Arm - 18"	Part No.: KIT01-599-000037
2 Years Recommended Spares Kit	Part No.: KIT01-599-000007
Toolkit	Part No.: KIT01-599-000130
Pneumatic Safety Unit (PSU)	Part No.: KIT01-599-000132

All dimensions and hydraulic requirements are for reference and may be subject to change without notice. Machine performance is subject to application and operator capability; please discuss your requirements directly with a Mactech sales representative. All information given and all sales made by Mactech Inc. are subject to their terms and conditions.

MACTECH INC.

4079 PEPIN AVE UNIT 4
RED WING MN 55066
800-328-1488
INFO@MACTECHONSITE.COM

MACTECH OFFSHORE

302 IDA ROAD Broussard La 70518 337-839-2793 Info@mactechoffshore.com

MACTECH KENTUCKY

3880 INDUSTRIAL DRIVE Paducah Ky 42001 270-442-1559 Info@mactechonsite.com

MACTECH WISCONSIN

2515 CLEVELAND AVE Marinette WI 54143 800-328-1488 Info@mactechonsite.com

MACTECH INTERNATIONAL

CONTACT US FROM ANYWHERE Around the World 337-839-2793 Info@Mactechoffshore.com

WORK SAFE WE REFORE ME WEI COME CHALLENGES WI

OPERATING DIMENSIONS:

FACING RANGE:			
Minimum Diameter	711.2mm	28"	
Maximum Diameter	1828.8mm	72"	


CLAMPING RANGE:			
Minimum Diameter	711.2mm	28"	
Maximum Diameter	1727mm	68"	

TECHNICAL DETAILS:			
Minimum Diameter	1300mm 51.1"		
Maximum Diameter	1880mm	74"	
Machine Height Above Flange	600mm 23.6"		
Toolpost Travel	40mm 1.6"		
Recommended Air Supply	6Bar @ 1.8m³/min 64cfm @ 87psi		
Noise Emission (Sound Power Level)	95dB(A)		

FEED RATES / POSITION:			
1	0.18mm	0.007"	
2	0.25mm	0.010"	
3	0.46mm	0.018"	
4	0.84mm	0.033"	

WEIGHTS:		
Machine Weight	454kg	999lbs
Transportation Weight	516kg	1135lbs

TRANSPORTATION DIMENSION	DNS:				
Ler	Length Width		dth	Н	eight
1140mm	44.9"	660mm	26"	830mm	32.7"



PHONE 337-839-2793 | EMAIL INFO@MACTECHONSITE.COM | WEB MACTECHONSITE.COM